



**Tolerances**

Shaft dia: f7 (< 55 mm id.)  
 h8 (> 55 mm id.)  
 Housing: H7

**Material: Triple-layer bushing**

Copper plated steel-layer (anti-corrosive)  
 Sintered, multiporous bronzelayer  
 Acetal plastic layer (with grease pockets)

Chamfer: Inner and outer ends

This document and its contents are the exclusive property of Lagermetall AB, and may not be copied, reproduced, transmitted or communicated to a third party, or used for any purpose without written permission.

|                        |   |                            |  |                   |                           |  |
|------------------------|---|----------------------------|--|-------------------|---------------------------|--|
|                        | <br>IRONCAD 2D drawing<br>3D model is available | General Tolerances acc to: | File Name:<br>440-POM-LMB.icd                      |                   |                           | Template Created Date:<br>2016-08-16 12:59 |
|                        |   | ISO 2768-mK                | Drawn by:<br>UP                                    | Weight g:<br>2.67 | Material:<br>Triple-layer |  |
| <br>www.lagermetall.se |   |                            | Wrapped triple-layer bearing<br>with acetalplastic |                   |                           | Sheet No:<br>1 ( 1 ) ...                   |
|                        |   |                            |  |                   |                           | Rev.<br>...                                |
|                        |   |                            | Doc. No:<br>440-POM1112LMB                         |                   |                           |  |