



**Tolerances**

Shaft dia: f7 (< 55 mm id.)  
 h8 (> 55 mm id.)  
 Housing: H7

**Material: Triple-layer bushing**

Copper plated steel-layer (anti-corrosive)  
 Sintered, multiporous bronzelayer  
 Acetal plastic layer (with grease pockets)

Chamfer: Inner and outer ends

This document and its contents are the exclusive property of Lagermetall AB, and may not be copied, reproduced, transmitted or communicated to a third party, or used for any purpose without written permission.

|                        |   |  |  |                            |                                  |   |
|------------------------|---|--|--|----------------------------|----------------------------------|---|
|                        | <br>IRONCAD 2D drawing<br>3D model is available | General Tolerances acc to:<br><b>ISO 2768-mK</b> | File Name:<br><b>440-POM-LMB.icd</b>               |                            |                                  | Template Created Date:<br><b>2016-08-16 12:59</b> |
|                        |   |  | Drawn by:<br><b>UP</b>                             | Weight g:<br><b>902.62</b> | Material:<br><b>Triple-layer</b> |   |
| <br>www.lagermetall.se |   |  | Wrapped triple-layer bearing<br>with acetalplastic |                            |                                  | Sheet No:<br><b>1 ( 1 ) ...</b>                   |
|                        |   |  |  |                            |                                  | Doc. No:<br><b>440-POM185100LMB</b>               |